




SEOYOUNG TECH. CO., LTD.

Renewable Energy Devices



Model-SYG-340-D-1500-300 AFPMG For HAWT or VAWT

No.	Parameter	Symbol	units	
1	Rectified DC Voltage	E	V	48
2	Gen. Output Voltage			AC (3Phase)
3	Rotor			Permanent magnet type (outer rotor)
4	Stator			Coreless
5	Output Power	P _o	W	1,500
6	Rated speed	ω	rpm	300
7	Speed Constant	K _E	V/krpm	176
8	Resistance (Line-Line)	R _T	Ω	0.22
9	Maximum Winding Temperature	C _{Max}	°C	130
10	Number of Pole	-	-	20
11	Winding type	-	-	Wye
12	Gen. Weight	W _M	Kg	34
13	Gen. Diameter	M _D	mm	340
14	Gen. Length	M _L	mm	120
15	Housing Material	-	-	Aluminum (Alloy)
16	Shaft Material	-	-	Steel
17	Shaft Bearing	-	-	Ball
18				
19				

APPLICATION – Small Wind Turbine, Hydro Power, etc.

SEOYOUNG TECH Co., Ltd.

#276, Gongdan-dong, Gumi City, Kyungbuk, Korea 730-030




Tel: +82-54-442-4040 Fax: +82-54-442-4060

e-mail: evsmotor@evsmotor.co.kr or www.evsmotor.co.kr



SEOYOUNG TECH. CO., LTD.

Renewable Energy Devices





SEOYOUNG TECH Co., Ltd.
#276, Gongdan-dong, Gumi City, Kyungbuk, Korea 730-030
Tel: +82-54-442-4040 Fax: +82-54-442-4060
e-mail: evsmotor@evsmotor.co.kr or www.evsmotor.co.kr



SEOYOUNG TECH. CO., LTD.

Renewable Energy Devices





SEOYOUNG TECH Co., Ltd.
#276, Gongdan-dong, Gumi City, Kyungbuk, Korea 730-030
Tel: +82-54-442-4040 Fax: +82-54-442-4060
e-mail: evsmotor@evsmotor.co.kr or www.evsmotor.co.kr



SEOYOUNG TECH. CO., LTD.

Renewable Energy Devices






Unit: mm

SEOYOUNG TECH Co., Ltd.
#276, Gongdan-dong, Gumi City, Kyungbuk, Korea 730-030
Tel: +82-54-442-4040 Fax: +82-54-442-4060
e-mail: evsmotor@evsmotor.co.kr or www.evsmotor.co.kr



SEOYOUNG TECH. CO., LTD.

Renewable Energy Devices



SEOYOUNG TECH Co., Ltd.
#276, Gongdan-dong, Gumi City, Kyungbuk, Korea 730-030
Tel: +82-54-442-4040 Fax: +82-54-442-4060
e-mail: evsmotor@evsmotor.co.kr or www.evsmotor.co.kr